

Product description	This is a top-coated thermal transfer printable platinum silver polyester film coated with a permanent high performance pressure sensitive acrylic adhesive and backed a double sides siliconised glassine release liner (adhesive coated on the less free (-9) release side)
----------------------------	---

Colours	1 - Glossy Aluminum
----------------	---------------------

PHYSICAL PROPERTIES

Product Data	Value	Test method
Thickness film	50 micron \pm 10%	ASTM D 3652
Thickness adhesive	35-37 micron \pm 3%	
Thickness liner	80 micron \pm 10%	
Dimension stability (%)	No shrinkage observed	On a panel at 70°C for 24hrs

ADHESION PROPERTIES**

Adhesion from (N/m)	Average	Test method
Stainless steel	1050	FTM 1 (Modified for 72 hr dwell time)
Expected shear (hours)	100+	FTM 8
Tack (gm/sq cm)	948	ASTM D 2979

**For guidance only. This data is based on limited test results due to the custom nature of this product, not to be used for setting specifications.

Expected exterior life:	Up to seven years (depending on
Service temperature:	conditions) -40°C to +150°C
Application temperature:	+10°C (min)
Storage stability:	Two years stored at 21°C and 50% RH

All of the descriptive information, the typical performance data, and recommendations for the use of Rebo B.V. products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Rebo B.V.. All purchasers of Rebo B.V. products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Rebo B.V. is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.